



SERVICING THE WORLD WITH HIGH TEMPERATURE TEXTILES

TDS – 46
January 2011

AVS SEWING THREAD SSS-18/PL

Product Description

AVS Sewing Thread SSS-18/PL is a high temperature resistant thread made by twisting together S-2 Fiberglass and a strand of Stainless Steel Wire.

Application

The thread is intended for high temperature sewing applications with service temperatures up to 1800°F (1000°C) requiring good seam strengths. The thread is ideal for sewing our FLXGLAS HT inorganic chemical treated Fiberglass Fabrics, our standard AVSil Silica Fabrics, and our ULTRAFLX HT inorganic chemical treated Silica Fabrics. Fabricated products include blankets, insulation pads, and curtains.

Technical Data

PROPERTIES

Construction
Coating
Lubrication
Diameter (inches)
Tensile
Final Twist
Yield

VALUE

S-2 Fiberglass/Stainless Steel Wire Strand
PTFE, 15% Nominal
Silicone Oil
0.019 nominal
25 lbs.
“Z”
1975 yds./lb.

AVS Industries, LLC cannot predict all of the potential applications for which customers may attempt to use the AVS Sewing Thread SSS-18/PL. AVS Sewing Thread SSS-18/PL will have varying degrees of effectiveness for each potential application depending on the maximum temperature attained, the length of use, and the amount of temperature fluctuation. If the customer has any questions regarding the use of AVS Sewing Thread SSS-18/PL in a particular application, please contact AVS Industries, LLC at (302) 221-1720 and we will provide a sample of the AVS Sewing Thread SSS-18/PL for testing. **This product is not warranted against injuries or damages of any kind caused by uses for which this product was not designed, intended, or tested by AVS Industries, LLC.**