



SERVICING THE WORLD WITH HIGH TEMPERATURE TEXTILES

TDS – 16
January 2015

SILICA SLEEVING

Product Description

Silica S-H Sleevings is silica tubing intended for use in high temperature applications as protection against weld splatter, fire, extreme heat and molten metal. **Silica S-H Sleevings** can withstand molten metal temperatures and equipment at continuous temperatures up to 1,800°F (1,000°C). **Silica S-H Sleevings** has a flexible weave that assures a “tight fit” over pipe, cable, hose, cord and tubing. **Silica S-H Sleevings** is used as thermal protection or insulation over: electrical cables, power cords, water hoses, tubing and pipe. Silica sleeving is used extensively by the Power Generation, Refinery, Construction, Shipbuilding, Welding and Metal Processing Industries.

Features

- Resists High Temperatures and Protects Against Weld “Splatter”
- Fireproof
- Excellent Insulating Properties

Benefits

- Protects Cables, Hoses, Pipe and Other Equipment in the Toughest Welding Applications
- Protects Against Hot Work Fires
- Lower Energy Costs

Sizing Data

PRODUCT SIZE

S-H-¼”

S-H-½”

S-H-1 ½”

S-H-2”

S-H-3”

S-H-4”

S-H-5”

S-H-6”

SLEEVING FITS OVER FOLLOWING I.D. RANGE

⅛” to ¼”

¼” to ½”

1¼” to 1⅝”

1¾” to 2”

2½” to 3½”

3½” to 4¼”

4¾” to 5½”

5½” to 6½”

Technical Data

PROPERTIES

Silicon Dioxide Content

Nominal Wall Thickness (inches)

Nominal Roll Length (ft)

SILICA S-H SLEEVING

96% or Greater

0.090

50

Notes:

1. Roll length tolerance is +/- 10%. Rolls may consist of three pieces. Minimum piece length is 10 feet. Other roll lengths are available upon request.
2. A light hydrocarbon coating is applied for improved handling at low temperatures.
3. Silica is made of amorphous silica textiles, and contains **no** asbestos or ceramic fibers.

AVS Industries, LLC cannot predict all of the potential applications for which customers may attempt to use the Silica Products. Silica Products will have varying degrees of effectiveness for each potential application depending on the maximum temperature attained, the length of use, and the amount of temperature fluctuation. If the customer has any questions regarding the use of Silica Products in a particular application, please contact AVS Industries, LLC at (302) 221-1720 and we will provide a sample of the Silica Products for testing. **This product is not warranted against injuries or damages of any kind caused by uses for which this product was not designed, intended, or tested by AVS Industries, LLC.**