



WHEN THE **HEAT** IS ON, KEEP YOUR COOL WITH **AVS!**

## Safety Data Sheet (SDS)

SDS-114  
May 2019

**Product: AVS Silica Silrub 84CH, AVS Silica Silrub 124CH, AVS Silica Silrub 188CH**

### 1. Chemical Product and Company Identification

**Trade Name:** AVS Silica Silrub 84CH, AVS Silica Silrub 124CH, AVS Silica Silrub 188CH

**Synonyms:** Silica Fabric, Silicone Coated, 1 & 2 sided

**Manufacturer:**

AVS Industries LLC  
21 Bellecor Drive  
Unit C  
New Castle, DE 19720

Phone Product Information (302) 221-1720  
Revision Date: May 31, 2019

**DESCRIPTION**

**No Hazard Rating is available for this Product.**

### 2. Hazard Identification

**Emergency Overview:**

Tan colored flexible woven fabric on one side, and red colored silicone coating on the reverse side, having no odor.

**Effects of Overexposure:**

**Eye Contact:** Slight irritation may be caused in contact with eyes.

**Skin Contact:** Temporary irritation of skin may be produced.

**Inhalation:** Inhalation of airborne fibers may cause irritation to the mouth, nose and throat.

**Ingestion:** May cause temporary irritation of the digestive tract, but not an expected route of entry in industrial uses.

**Chronic Hazards:** There are no known chronic health effects associated with the use of this product under normal working conditions.

**Primary Routes of Entry:** Skin contact, inhalation, ingestion & eye contact.

**Carcinogenicity Information:** The Silicone Coating Only Part A contains  $\leq 0.4\%$  quartz (crystalline silica). Crystalline silica is suspected human carcinogen per ACGIH, and a IARC Group 1 human carcinogen.

**Product: AVS Silica Silrub 84CH, AVS Silica Silrub 124CH & AVS Silica Silrub 188CH**

**3. Composition and Information on Ingredients**

<b>Ingredient(s)</b>	<b>CAS Number</b>	<b>Approx. Percent</b>
Amorphous Silica	7631-86-9	95%
Proprietary Finish Triethylene Amine	121-44-8	<0.2%

Silicone System  
Composition – Mixture of Polyorganosiloxanes, fillers & additives

<b>Common Name and Synonyms</b>	<b>CAS Number</b>	<b>Approx. Percent</b>
Octamethyl Cyclo Tetra Siloxane D4	556-67-2	0.1-1%

Fillers and additives encapsulated in a polymer are not expected to pose a health hazard when processed under normal conditions of use.

**4. First Aid Information**

Eye Contact: Flush eyes immediately with large amounts of water for at least 15 minutes holding eyelids open while flushing. Seek medical attention promptly.

Skin Contact: Wash contaminated skin thoroughly with mild soap and cool water. Seek medical attention if irritation persists.

Inhalation: Remove person from source of exposure and then seek medical attention immediately.

Ingestion: Seek medical attention immediately.

**5. Fire Fighting Measures**

Flash Point: N.A.  
Lower Explosive Limit (%): N.A.  
Upper Explosive Limit (%): N.A.

Autoignition Temperature: N.D.

Extinguishing Media: Carbon dioxide, water, foam or dry chemical for type of surrounding fire.

Unusual Fire & Explosion Hazards: During sustained fire the following hazardous decomposition products may be evolved: silicon dioxide, metal oxides, quartz, carbon dioxide, traces of incompletely burned carbon products and formaldehyde.

Fire Fighting Instructions: Wear full fire fighting protective equipment including self-contained breathing apparatus.

**6. Accidental Release Measures**

Step to be taken in case material is released or spilled:

Dust or loose fibers can be vacuumed or swept with the aid of a dust suppressant.

Dispose according to federal, state, and local environmental regulations.

**Product: AVS Silica Silrub 84CH, AVS Silica Silrub 124CH & AVS Silica Silrub 188CH**

**7. Handling and Storage**

Store material in a clean dry place, and keep container closed. Store away from oxidizing materials.

Particular care should be taken when working with "used" material to minimize dust. If exposure limits are exceeded or if irritation is experienced, NIOSH approved respiratory protection should be worn.

**8. Exposure Controls and Personal Protection**

**ENGINEERING CONTROLS:**

Ventilation: General ventilation and/or local exhaust ventilation are adequate.

Respiratory Protection: Respirators are not necessary under normal working conditions.

Eye Protection: Eye protection is not necessary under normal working conditions.

Protective Clothing: Protective Clothing is not necessary under normal working conditions.

Hygienic Practices: Use good personal hygiene practices.

**EXPOSURE LIMITS:**

Product

Amorphous Silica

PEL (OSHA) 80mg/m<sup>3</sup> ÷ % SiO<sub>2</sub> or 20 mppcf

TLV (ACGIH) 10 mg/m<sup>3</sup> (inhalable fraction); 3 mg/m<sup>3</sup> (respirable)

NIOSH 6 mg/m<sup>3</sup>

IDHL 3000 mg/m<sup>3</sup>

Silicone

Dimethylsiloxane, dimethylvinyl-terminated

N.E.

Calcium Carbonate treated with stearic acid

\*PEL (OSHA) 15 mg/m<sup>3</sup> (total); 5 mg/m<sup>3</sup> (respirable)

\*TLV (ACGIH) 10 mg/m<sup>3</sup>

\*Exposure limits for calcium carbonate only.

Alumina Hydrate

N.E.

Dimethylcyclosiloxanes

N.E.

Quartz

PEL (OSHA) 10 mg/m<sup>3</sup> ÷ % SiO<sub>2</sub>+2 (respirable)

30 mg/m<sup>3</sup> ÷ % SiO<sub>2</sub>+2 (total)

TLV (ACGIH) 0.05 mg/m<sup>3</sup> (respirable)

IDLH 50 mg/m<sup>3</sup>

Dimethyl, methylhydrogen siloxane

N.E.

Decamethylcyclopentasiloxane

N.E.

Silicone & Red Pigment Ingredients

Dimethylsiloxane, dimethylvinyl-terminated

N.E.

**Product: AVS Silica Silrub 84CH, AVS Silica Silrub 124CH & AVS Silica Silrub 188CH**

Titanium Dioxide  
PEL (OSHA) 15 mg/m<sup>3</sup>  
TLV (ACGIH) 10 mg/m<sup>3</sup>

Chromium, III  
PEL NIOSH/(OSHA) 0.5 mg/m<sup>3</sup>  
TLV (ACGIH) 0.5 mg/m<sup>3</sup>  
IDLH 25 mg/m<sup>3</sup>

Antimony & Compounds (as Sb)  
PEL (OSHA) 0.5 mg/m<sup>3</sup>  
TLV (ACGIH) 0.5 mg/m<sup>3</sup>

**9. Physical and Chemical Properties**

PHYSICAL DATA:  
Boiling Point: 4046° F  
Melting Point: >3000° F  
Solubility in Water: Insoluble  
Vapor Pressure: N.D.  
Vapor Density: N.D.  
Specific Gravity: 2.2  
Color: Tan colored one side; reverse side red  
Odor: None  
Physical State: Woven Fabric coated on one side with silicone.

**10. Stability and Reactivity**

Chemical Stability: Product is stable at normal temperature and storage conditions.

Incompatibilities:

Silica Fabric: Basic phosphates, hydrofluoric acid, and some oxides and hydroxides.

Silicone Coating: Oxidizing materials can cause a reaction.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Hazardous Decomposition Products (Silicone Coating Only): Thermal breakdown of this product during very high heat conditions may evolve the following hazardous decomposition products: carbon oxides and traces of incompletely burned carbon compounds, silicone dioxide, metal oxides, quartz and formaldehyde.

**11. Toxicological Information**

Material which has been subjected to elevated temperatures (>1800°F) may undergo partial conversion to cristobalite, a form of crystalline silica, which may cause respiratory illness. The amount of cristobalite present will depend on the temperature and length of service. The OSHA PEL for cristobalite is 0.05 mg/m<sup>3</sup> (respirable).

**12. Ecological Information**

No information is available; however, toxicity is expected to be low based on the insolubility in water of the product.

**13. Disposal Considerations**

Dispose of waste material in accordance with applicable federal, state, and local environmental regulations.

**Product: AVS Silica Silrub 84CH, AVS Silica Silrub 124CH & AVS Silica Silrub 188CH**

**14. Transportation Information**

DOT Proper Shipping Name: Silica Fabric, Silicone Coated  
DOT Hazardous Class: None  
DOT UN/NA Number: None  
Emergency Response Guide Number: None

**15. Regulatory Information**

U.S. FEDERAL REGULATIONS AS FOLLOWS:

SARA Section 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372: Chromium compounds, Antimony compounds

TSCA: The chemical substances in this product are on the TSCA Section 8 Inventory.

EXPORT NOTIFICATION: This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States: None

INTERNATIONAL REGULATIONS AS FOLLOWS:

Canadian WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Canadian WHMIS CLASS: Not Regulated.

DSL: The chemical substances in this product are listed on the Domestic Substances List (DSL).

**16. Other Information**

This Material Safety Data Sheet was revised in its entirety in May 2019.

ABBREVIATIONS:

- 1) ACGIH – American Conference of Governmental Industrial Hygienists
- 2) OSHA – Occupational Safety and Health Administration
- 3) NIOSH – National Institute of Occupational Safety and Health
- 4) IARC – International Agency for Research on Cancer
- 5) NTP – National Toxicology Program
- 6) TLV – Threshold Limit Value
- 7) PEL – Permissible Exposure Limit
- 8) TWA – Time Weighted Average
- 9) STEL – Short Term Exposure Limit
- 10) IDHL – Immediately Dangerous to Life or Health
- 11) N.A. – Not Applicable
- 12) N.D. – Not Determined
- 13) N.E. – Not Established
- 14) DSL – Domestic Substances List

THE ABOVE INFORMATION IS BELIEVED TO BE ACCURATE BASED ON THE MOST CURRENT DATA AVAILABLE. AVS INDUSTRIES MAKES NO WARRANTY, EITHER EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND ASSUMES NO LIABILITY RESULTING FROM ITS USE. USERS ARE ADVISED TO CONDUCT THEIR OWN TESTS TO DETERMINE THE SAFETY AND SUITABILITY OF EACH PRODUCT OR PRODUCT COMBINATION FOR THEIR OWN PURPOSES. AVS INDUSTRIES SHALL NOT BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR INCIDENTAL OR CONSEQUENTIAL DAMAGES, HOWSOEVER ARISING EVEN IF AVS INDUSTRIES HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.